

MATERIAL SAFETY DATA SHEET
ZOOM SPOUT OILER
Panef Inc.

Page 1 of 5

Revision Date: 01/01/09

Section 1: Chemical Product and Company Identification

Product Name: 76 Turbine Oil 32	Product Number: SO-70
Manufacturer: Panef Inc. 5700 West Douglas Ave. Milwaukee, WI 53218	Emergency Telephone: 800-535-5053
Total Pages: 5	Information Telephone: 414-464-7200

Section 2: Composition / Information on Ingredients

No hazardous components identified per 29 CFR 1920.1200.

<u>Other Components</u>	<u>% Volume</u>	<u>Exposure Guideline</u>		
		<u>Limits</u>	<u>Agency</u>	<u>Type</u>
Lubricant Base Oil (Petroleum) Cas# Various	<95	(See: Oil Mist, if Generated)		
Additives Cas# Proprietary	<5	Not Established		

<u>Reference</u>	<u>Exposure Guideline</u>		
	<u>Limits</u>	<u>Agency</u>	<u>Type</u>
Oil Mist, if Generated Cas# None	5 mg/m3 10 mg/m3 5 mg/m3 2500 mg/m3	ACGIH ACGIH OSHA NIOSH	TWA STEL TWA IDLH

The base oil for this product can be a mixture of any of the following highly refined petroleum streams:
CAS 64741-88-7; CAS 64741-89-5; CAS 64741-96-4; CAS 64741-97-5; CAS 64742-01-4; CAS 64742-52-5;
CSA 64742-53-6; CAS 64742-54-7; CAS 64742-55-8; CAS 64742-56-9; CAS 64742-57-0; CAS 64742-62-7
CAS 64742-63-8; CAS 64742-65-0; CAS 72623-85-9; CAS 72623-86-0; CAS 72623-87-1

Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.

Section 3: Hazards Identification

Potential Health Effects:

Eyes: Contact may cause mild eye irritation including stinging, watering, and redness.

Skin: Contact may cause mild skin irritation including redness, and a burning sensation. Prolonged or repeated contact can worsen irritation by causing drying and creaking of the skin leading to dermatitis (inflammation). No harmful effects from skin absorption are expected.

Inhalation (Breathing): No information available. Studies by other exposure routes suggest a low degree of toxicity by inhalation.

Ingestion (Swallowing): No harmful effects expected from ingestion.

Signs and Symptoms: Effects of overexposure may include irritation of the nose and throat, irritation of the digestive tract, nausea and diarrhea.

Cancer: Inadequate evidence available to evaluate the cancer hazard of this material. See Section 11 for carcinogenicity information of individual components, if any.

Target Organs: No data available for this material.

Developmental: No data available for this material.

Pre-Existing Medical Conditions: Conditions aggravated by exposure may include skin disorders

Material Safety Data Sheet

ZOOM SPOUT OILER

Page 2 of 5

Revision Date: 01/01/09

Section 4: First Aid Measures

Eyes: If irritation or redness develops, move victim away from exposure and into fresh air. Flush eyes with clean water. If symptoms persist, seek medical attention.

Skin: Wipe material from skin and remove contaminated shoes and clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water and, if necessary, a waterless skin cleanser. If irritation or redness develops and persists, seek medical attention.

Ingestion (Swallowing): First aid is not normally required; however, if swallowed and symptoms develop, seek medical attention.

Inhalation (Breathing): If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, clear airway and immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

Note To Physicians: High-pressure hydrocarbon infection injuries may produce substantial necrosis of underlying tissue despite an innocuous appearing external wound. Often these injuries require extensive emergency surgical debridement and all injuries should be evaluated by a specialist in order to assess the extent of injury.

Section 5: Fire Fighting Measures

Flammable Properties: Flash Point: >365°F/>185°C (COC)
OSHA Flammability Class: Not applicable
LEL/UEL%: No Data
Autoignition Temperature: No Data

Unusual Fire & Explosion Hazard: This material may burn, but will not ignite readily. Vapors are heavier than air and can accumulate in low areas. If container is not properly cooled, it can rupture in the heat of fire.

Extinguishing Media: Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.

Fire Fighting Instructions: For fires beyond the incipient stage, emergency responders in the immediate hazard area should wear bunker gear. When the potential chemical hazard is unknown, in enclosed or confined spaces, or when explicitly required by DOT, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (See Section 8).

Isolate immediate hazard area, keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Move undamaged containers from immediate hazard area if it can be done with minimal risk.

Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done with minimal risk. Avoid spreading burning liquid with water used for cooling purposes.

Section 6: Accidental Release Measures

This material may burn, but will not ignite readily. Keep all sources of ignition away from spill/release. Stay upwind and away from spill/release. Notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant (See Section 8).

Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems, and natural waterways. Dike far ahead of spill for later recovery or disposal. Spilled material may be absorbed into an appropriate absorbent material.

Notify fire authorities and appropriate federal, state and local agencies. Immediate cleanup of any spill is recommended. If spill of any amount is made into or upon navigable waters, the contiguous zone, or adjoining shorelines, notify the National Response Center (phone number 800-424-8802).

Material Safety Data Sheet

ZOOM SPOUT OILER

Page 3 of 5

Revision Date: 01/01/09

Section 7: Handling and Storage

Handling: Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146. The use of appropriate respiratory protection is advised when concentrations exceeds any established exposure limits (See Section 2 & 8).

Do not wear contaminated clothing or shoes. Use good personal hygiene practice.

Do not use this product or other hydrocarbon-based lubricants in non-diaphragm compressors that produce "breathing air" unless the outlet air is monitored continuously for carbon monoxide. These lubricants can produce carbon monoxide when subjected to high temperatures.

High pressure injection of hydrocarbon fuels, hydraulic oils or greases under the skin may have serious consequences even though no symptoms or injury may be apparent. This can happen accidentally when using high pressure equipment such as high pressure grease guns. Fuel injection apparatus or from pinhole leaks in tube of high pressure hydraulic oil equipment.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

Before working on or in tanks which contains or have contained this material, refer to OSHA regulations, ANSI Z49.1 and other references pertaining to cleaning, repairing, welding, or other contemplated operations.

Storage: Keep containers(s) tightly closed. Use and store this material in cool, dry, well-ventilated areas away from heat and all sources of ignition. Store only in approved containers. Keep away from any incompatible material (See Section 10). Protect container (s) against physical damage.

Section 8: Exposure Controls / Personal Protection

Engineering Controls: If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits (See Section 2), additional ventilation or exhaust system may be required.

Personal Protective Equipment (PPE):

Respiratory: A NIOSH certified air purifying respirator with a Type 95 (R or P) particulate filter may be used under conditions where airborne concentrations are expected to exceed exposure limits (See Section 2). Protection provided by air purifying respirators is limited (see manufacturer's respirator selection guide). Use a positive pressure air supplied respirator if there is potential for uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA's 29CFR 1910.134 and ANSI Z 88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Skin: The use of gloves impervious to the specific material handled is advised to prevent skin contact and possible irritation (see manufacturer's literature for information on permeability).

Eye/Face: Approved eye protection to safeguard against potential eye contact, irritation, or injury is recommended. Depending on conditions of use, a face shield may be necessary.

Other Protective Equipment: A source of clean water should be available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.

Section 9: Physical / Chemical Characteristics

Note: Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm).

Flash Point: >365°F/>185°C (COC)
Flammable/Explosive Limits (%): No Data
Autoignition: Temperature: No Data
Appearance: Clear Yellow
Physical State: Liquid
Odor: Characteristic Petroleum

Material Safety Data Sheet

ZOOM SPOUT OILER

Page 4 of 5

Revision Date: 01/01/09

Section 9: Physical / Chemical Characteristics

Ph: Not applicable
Vapor Pressure (mm Hg): <1
Vapor Density (air=1): >1
Boiling Point/Range: >555°F/>291°C
Freezing/Melting Point: No Data
Solubility in Water: Negligible
Specific Gravity: 0.86-0.88
Percent Volatile: Negligible
Evaporation Rate (nBuAc=1): <1
Viscosity: 30.3-32.2cSt @ 40°C
Bulk Density: 7.33 lbs/gal

Section 10: Stability and Reactivity

Chemical Stability: Stable under normal conditions of storage and handling.
Conditions to Avoid: Extended exposure to high temperatures can cause decomposition.
Incompatible Materials: Avoid contact with strong oxidizing agents.
Hazardous Decomposition Products: Combustion can yield aldehydes and carbon, nitrogen and sulfur oxides. Thermal decomposition may produce hydrogen sulfide and other sulfur-containing gases at temperatures greater than 150°F. Methacrylate monomers may also be formed.
Hazardous Polymerization: Will not occur.

Section 11: Toxicology Information

Lubricant Base Oil (Petroleum) (CAS# Various)

Carcinogenicity: The petroleum bas oils contained in this product have been highly refined by a variety of processes including solvent extraction, hydrotreating, and dewaxing to remove aromatics and improve performances characteristics. None of the oils used are listed as a carcinogen by NTP, IARC, or OSHA.

Section 12: Ecological Information

None Available

Section 13: Disposal Considerations

This material under most intended uses would become used oil due to contamination by physical or chemical impurities. RECYCLE ALL USED OIL. While being recycled, used oil is regulated by 40 CFR 279. Use resulting in chemical or physical change or contamination may also subject it to regulation as hazardous waste. Under federal regulations, used oil is a solid waste managed under 40 CFR 279. However, in California, used oil is managed as hazardous waste until tested to show it is not hazardous. Consult state and local regulations regarding the proper handling of used oil. In the case of used oil, the intent to discard it may cause the used oil to be regulated as hazardous waste.

Contents should be completely used and containers emptied prior to discard. Rinsate may be considered a RCRA hazardous waste and must be disposed of with care and in compliance with federal, state and local regulations. Large empty containers, such as drums, should be returned to the distributor or a drum reconditioner. To assure proper disposal of small empty containers, consult with state and local regulations and disposal authorities.

Section 14: Transportation Information

Hazard Class or Division: Not Classified as Hazardous

Material Safety Data Sheet

ZOOM SPOUT OILER

Page 5 of 5

Revision Date: 01/01/09

Section 15: Regulatory Information

This material contains the following chemicals subject to the reporting requirements of SARA 313 and 40 CFR 372: None

Warning: This material contains the following chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm, and are subject to the requirements of **California Proposition 65** (CA Health & Safety Code Section 25249.5): None known

This material has not been identified as a carcinogen by NTP, IARC or OSHA. See Section 11 for carcinogenicity information of individual components, if any. EPA (Cercla) Reportable Quantity: None

Section 16: Other Information

Disclaimer: The information contained herein is based on data available. However, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from use thereof. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use.